



## GRAS VAN DE BUREN



### Technical specification | Alvera

<b>Type</b>	: tufted non filled synthetic grass carpet	
<b>Yarn material</b>	: PE monofilament straight, PE monofilament non directional & PP monofilament curled	
<b>Yarn type</b>	: 16.500/24 dTex : combination of V-shape non directional, C-shape and oval shape texturized	
<b>Yarn quality</b>	: environmental friendly, UV stabilized, UV stability meets DIN 53387 standard : free of lead and cadmium	
<b>Colour fastness</b>	: xenon test: blue scale > 7, grey-scale > 4	
<b>Primary backing</b>	: 100% PP Thiobac ® with fleece, black, UV stabilized : weight 155 gr/m <sup>2</sup>	
<b>Secondary backing</b>	: black latex compound with a base of styrene-butadiene (SBR), with drainage holes : weight 850 gr/m <sup>2</sup>	
<b>Tuft gauge</b>	: 3/8"	
<b>Pile height</b>	: 45mm	(+/-10%)
<b>Stitches per 10cm</b>	: 12.0	(+/-10%)
<b>Stitches per m<sup>2</sup></b>	: 12.600	(+/-10%)
<b>Face weight</b>	: 2.050 gr/m <sup>2</sup>	(+/-10%)
<b>Total weight</b>	: 3.055 gr/m <sup>2</sup>	(+/-10%)
<b>Roll width</b>	: 400cm + 200cm	(+/- 2cm)
<b>Roll length</b>	: 25.20 m <sup>1</sup>	(+/- 20cm)
	: roll length may vary	
<b>Water permeability</b>	: 60 liter/min/m <sup>2</sup>	
<b>Fire retardant classification</b>	: Cfl-S1 (EN ISO 11925-2: sand filled ca. 5mm) : Efl-S1 (EN ISO 11925-2; non filled)	
<b>Batch information</b>	: before installation please make sure the batch numbers (AVL-....) are equal	
<b>Shrinkage</b>	: shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting	
<b>Infill recommendation</b>	: non infill (optional 5kg/m <sup>2</sup> )	

Het gras van de buren is altijd groener!

[www.grasvdburen.nl](http://www.grasvdburen.nl)